

Technical Datasheet

AC C-TEC 2403-1



DC-UPS
NCPA0724G01001

1 Short description

The buffered DC power supply of the **AC C-TEC** series includes ultra-capacitors as energy storage inside the housing. During normal operation this capacitor is charged from AC-mains. The connected DC consumers are supplied as well from AC mains. In case of an interruption of the AC supply, the energy of the ultra-capacitor is released regulated. With a dc/dc converter the load is supplied from the capacitor until it is discharged. The backup time depends on the state of charge of the capacitor and the discharge current.

The power supply has the following characteristics:

- Maintenance-free because of long-life ultra-capacitors
- Mikrocontroller based charging and discharging of the ultra-capacitors
- Control of operation and status of charge with potential-free contacts and LED
- Capacity extension possible with external capacitor extension modules

2 Technical Data

| | |
|---|---|
| Nominal input voltage | 115 V ... 230 V AC ($\pm 15\%$) |
| Input voltage range for charging operation | 97,8 V ... 264,5 V AC |
| Nominal frequency | 47 Hz ... 63 Hz |
| Max. nominal input current | 0,84 A @ 115VAC 0,42 A @ 230 V AC |
| Max. inrush current | 30 A / 2 ms |
| Nominal output current max. | 3 A DC (bei 0,47 kJ) |
| Nominal output current at max. energy | 2 A DC (bei 0,5 kJ) |
| Current limitation | 1,05 ... 1,5 x I_{Nenn} |
| Nominal output voltage (in mains operation) | 24,3 VDC $\pm 2\%$ |
| Output voltage (in back-up operation) | 23,5 VDC $\pm 2\%$ |
| Energy | 500 J |
| Max power loss ,worst-case' | 12 W |
| efficiency | 88% @ ($U_e=230$ V AC; $U_a=24,3$ V DC; $I_a=I_{Nenn}$) |
| Internal device protection | 2,5 A (T), 250 V |
| Fuse DC-output circuit (external) | 3,15 A (T) |
| Type of connection: input U_e | screw terminal max. 2,5 mm ² 0,4 Nm |
| Type of connection: output U_a | screw terminal max. 2,5 mm ² 0,4 Nm |
| Type of connection: message contact | screw terminal max. 2,5 mm ² 0,4 Nm |
| Max. load message contact ($U_e\text{-OK}^1$) | 30 V / 0,5 A potentialfree relay contact |
| Max. load message contact ($U_c >^1$) | 30 V / 0,5 A potentialfree relay contact |

¹ The message contacts are coupled with the LED display. The illumination of a LED effects the activation of the corresponding relay.

Technical Datasheet

AC C-TEC 2403-1



J. Schneider
Elektrotechnik

| | |
|---|-----------------------------------|
| Protective system | IP20 u. EN 60529 |
| Environmental temperature | -40 °C ... 60 °C |
| Storage temperature | -40 °C ... 60 °C |
| Rel. humidity | ≤95% condensation not permissible |
| Max. mounting height (without load reduction) | 2000 m ü. NN |
| Dimensions (H x W x D) | 152,5 mm, 72 mm, 130 mm |
| weight | 0,85 Kg |

3 Norms and regulations

| | |
|-----------------------|---|
| Terminal voltage | SELV / PELV according to EN 50178 |
| Ermitted interference | EN 6100-3-2 EN 6100-3-3 class A EN 55011 class B EN 62040 -2 |
| Noise immunity | EN 61000-6-2 EN 62040-2 EN 61000-4-2 EN 61000-4-3 EN 61000-4-4 EN 61000-4-5 EN 61000-4-6 EN 61000-4-11 |
| Total unit | EN 50178 EN 61010-1 / EN 61010-2-201 EN 62368-1 UL 508 / C22.2 |