



DC-UPS

NCPA0724G01020

1 Short description

The buffered DC power supply of the **AC C-TEC** series includes ultra-capacitors as energy storage inside the housing. During normal operation this capacitor is charged from AC-mains. The connected DC consumers are supplied as well from AC mains. In case of an interruption of the AC supply, the energy of the ultra-capacitor is released regulated. With a dc/dc converter the load is supplied from the capacitor until it is discharged. The backup time depends on the state of charge of the capacitor and the discharge current.

The power supply has the following characteristics:

- Maintenance-free because of long-life ultra-capacitors
- Microcontroller based charging and discharging of the ultra-capacitors
- Control of operation and status of charge with potential-free contacts and
- LED Capacity extension possible with external capacitor extension modules

2 Technical Data

Nominal input voltage	400 V AC ($\pm 15\%$)
Input voltage range for charging operation	340V...460VAC
Nominal frequency	47 Hz ... 63 Hz
Max. nominal input current	0,2A@400VAC
Max. inrush current	30 A / 2 ms
Nominal output current max.	3 A DC (bei 0,94 kJ)
Nominal output current at max. energy	2 A DC (bei 1,0 kJ)
Current limitation	1,05 ... 1,5 x I_{Nenn}
Nominal output voltage (in mains operation)	24,3VDC $\pm 2\%$
Output voltage (in back-up operation)	23,5VDC $\pm 2\%$
Energy	1 kJ
Max power loss ,worst-case'	12 W
efficiency	88% @ ($U_e=400$ V AC; $U_a=24,3$ V DC; $I_a=I_{Nenn}$)
Internal device protection	2,5 A (T), 250 V
Fuse DC-output circuit (external)	3,15A (T)
Type of connection: input U_e	screw terminal max. 2,5 mm ² 0,6 Nm
Type of connection: output U_a	screw terminal max. 2,5 mm ² 0,6 Nm
Type of connection: message contact	screw terminal max. 2,5 mm ² 0,6 Nm
Max. load message contact ($U_e\text{-OK}^1$)	30 V/ 0,5 A potentialfree relay contact
Max. load message contact ($U_c >^1$)	30 V/ 0,5 A potentialfree relay contact
Protective system	IP20 u. EN 60529
Environmental temperature	-20 °C ... 60 °C

¹ The message contacts are coupled with the LED display. The illumination of a LED effects the activation of the corresponding relay.

Technical Datasheet

AC C-TEC 2403-1-400



J. Schneider
Elektrotechnik

Storage temperature	-20 °C ... 60 °C
Rel. humidity	≤95% condensation not permissible
Max. mounting height (without load reduction)	2000 m ü. NN
Dimensions (H x W x D)	152,5 mm, 102 mm, 130 mm
weight	2,2 Kg

3 Norms and regulations

Terminal voltage	SELV / PELV according to EN 60204-1
Ermittled interference	EN 6100-3-2 EN 6100-3-3 class A EN 55011 class B EN 62040 -2
Noise immunity	EN 61000-6-2 EN 61000-4-2 EN 61000-4-3 EN 61000-4-4 EN 61000-4-5 EN 61000-4-6 EN 61000-4-11 EN 62040-2
Complete device	EN 50178 EN 61010-1 / EN 61010-2-201 EN 62368-1