

# Technical Datasheet

## C-TEC 2403-1



### DC-UPS NCPA0727G01002

#### 1 Short description

The DC-UPS of the series **C-TEC** includes ultra-capacitors as energy storage inside the housing. This capacitor is charged with the system voltage ( $U_e$ ) during normal operation. The connected loads are supplied as well from the system voltage. In case of an interruption of the system voltage the energy of the ultra-capacitors is released in a regulated way. With a dc dc converter, the load is supplied by the capacitor until it is discharged. The back-up time depends on the state of charge of the capacitors and on the discharge current.

#### The DC-UPS has the following characteristics:

- Maintenance-free because of long-life ultra-capacitors
- Microcontroller based charging and discharging of the ultra-capacitors
- Control of operation and status of charge with potential-free contacts and LED
- Capacity extension possible with external capacitor extension modules

#### 2 Technical Data

Nominal input voltage	24VDC-1,2%/+15% SELV/PELV according to 60204-1
Input voltage range	23,7 V DC...27,6 V DC
Min. charging voltage	23,7 V DC
Nominal input current (at 24,0 V DC) C charged 3 A load	3,1 A DC
Output voltage in back-up operation	23,0 V DC ± 2 %
Nominal output current Max	3 A DC (at 0,94 kJ)
Nominal output current at maximum energy	2 A DC (at 1,0 kJ)
Current limitation	1,05 ... 1,2 x $I_{Nom}$
Power loss at $U_c >$	2,5 W
Power loss at 100 % load and charge	7 W (max. 60 seconds)
Efficiency at $U_c >$	>96% @ ( $U_e=24,0$ V DC; $U_a=22,9$ V DC; $I_a=I_{Nom}$ )
Internal device protection (internal)	4A(T)
fusing DC-output circuit (external)	3A(T)
Type of connection: input $U_e$	Spring terminal max. 1,0 mm <sup>2</sup>
Type of connection: output $U_a$	Spring terminal max. 1,0 mm <sup>2</sup>
Type of connection: message contacts	Spring terminal max. 1,0 mm <sup>2</sup>
Max. load message contact ( $U_e$ -OK <sup>1</sup> )	30 V / 0,5 A potential-free relay-contact
Protective system	IP20 u. EN 60529
Operational temperature	-20 °C ... 60 °C
Storage temperature	-20 °C ... 60 °C
Rel. humidity	≤95% no condensation
Max. mounting height (without load reduction)	2000 m above sea level
dimensions (HxWxD)	92,5 mm, 60 mm, 116 mm
weight	0,6 Kg

<sup>1</sup> The message contacts are coupled with LED display. (see section 4.1). The illumination of a LED effects the activation of the corresponding relay.

# Technical Datasheet

## C-TEC 2403-1



### 3 Norms and regulations

Terminal voltage	SELV / PELV according to EN 60204-1
Emitted interference	EN 6100-3-2 EN 6100-3-3 class A EN 55011 class B EN 62040 -2
Noise immunity	EN 61000-6-2 EN 62040-2  EN 61000-4-2 (Static discharge ESD) 8kV/6kV EN 61000-4-3 (Electromagnetic fields) 10V/m 27 – 1000MHz 3V/m 1400 - 2700MHz EN 61000-4-4 (fast transients / Burst) DC IN, DC OUT 2kV others 1kV EN 61000-4-5 ( Surge) DC IN 0.5kV EN 61000-4-6 (conducted immunity) 10V 150kHz – 80MHz EN 61000-4-11 (voltage interruptions) back-up with ultra capacitor
Total unit	EN 50178 EN 61010-1 / EN 61010-2-201 EN 62368-1 UL 508